

BEAM CONVERSIONS TO WESTERN SPECIES GLULAM

Glued Laminated Timber Design Values

Steel Design Values (AISC, 9th edition, ASD)

Simple Span Beam

$$F_{bx} = 2400 \text{ psi}$$

$$F_v = 50 \text{ ks}$$

Dry Service Conditions

$$E_x = 1,800,000 \text{ psi}$$

$$F_b = 0.66 * F_v$$

$$E = 29,000 \text{ ks}$$

Glulam Beam Dimensions Are in Inches

Steel Section	Glulam Sizes to Substitute for Use in Floor Systems						Glulam Sizes to Substitute for Use in Roof Systems with Snow Loads						Glulam Sizes to Substitute for Use in Roof Systems with Non-Snow Loads					
	Floor Systems			C _D = 1.0			Roof Systems with Snow Loads			C _D = 1.15			Roof Systems with Non-Snow Loads		C _D = 1.25			
W 6 x 9	3 1/8	x	13 1/2	5 1/8	x	10 1/2	6 3/4	x	9	3 1/8	x	12	5 1/8	x	9	6 3/4	x	9
W 8 x 10	3 1/8	x	15	5 1/8	x	12	6 3/4	x	10 1/2	3 1/8	x	13 1/2	5 1/8	x	12	6 3/4	x	10 1/2
W 8 x 15	3 1/8	x	18	5 1/8	x	15	6 3/4	x	13 1/2	3 1/8	x	18	5 1/8	x	13 1/2	6 3/4	x	12
W 12 x 14	3 1/8	x	21	5 1/8	x	16 1/2	6 3/4	x	15	3 1/8	x	19 1/2	5 1/8	x	15	6 3/4	x	15
W 12 x 16	3 1/8	x	22 1/2	5 1/8	x	18	6 3/4	x	15	3 1/8	x	21	5 1/8	x	16 1/2	6 3/4	x	15
W 12 x 19	--	x	--	5 1/8	x	19 1/2	6 3/4	x	18	3 1/8	x	24	5 1/8	x	18	6 3/4	x	16 1/2
W 10 x 22	--	x	--	5 1/8	x	21	6 3/4	x	18	--	x	--	5 1/8	x	19 1/2	6 3/4	x	16 1/2
W 12 x 22	--	x	--	5 1/8	x	22 1/2	6 3/4	x	19 1/2	--	x	--	5 1/8	x	21	6 3/4	x	16 1/2
W 14 x 22	--	x	--	5 1/8	x	24	6 3/4	x	21	--	x	--	5 1/8	x	22 1/2	6 3/4	x	18
W 12 x 26	--	x	--	5 1/8	x	25 1/2	6 3/4	x	22 1/2	--	x	--	5 1/8	x	24	6 3/4	x	19 1/2
W 14 x 26	--	x	--	5 1/8	x	27	6 3/4	x	22 1/2	--	x	--	5 1/8	x	24	6 3/4	x	21
W 16 x 26	--	x	--	5 1/8	x	27	6 3/4	x	24	--	x	--	5 1/8	x	25 1/2	6 3/4	x	21
W 12 x 30	--	x	--	5 1/8	x	28 1/2	6 3/4	x	24	--	x	--	5 1/8	x	25 1/2	6 3/4	x	21
W 14 x 30	--	x	--	5 1/8	x	28 1/2	6 3/4	x	25 1/2	--	x	--	5 1/8	x	27	6 3/4	x	22 1/2
W 16 x 31	--	x	--	5 1/8	x	31 1/2	6 3/4	x	27	--	x	--	5 1/8	x	28 1/2	6 3/4	x	24
W 14 x 34	--	x	--	5 1/8	x	31 1/2	6 3/4	x	27	--	x	--	5 1/8	x	28 1/2	6 3/4	x	24
W 18 x 35	--	x	--	5 1/8	x	34 1/2	6 3/4	x	30	--	x	--	5 1/8	x	31 1/2	6 3/4	x	27
W 16 x 40	--	x	--	5 1/8	x	37 1/2	6 3/4	x	31 1/2	--	x	--	5 1/8	x	34 1/2	6 3/4	x	28 1/2
W 21 x 44	--	x	--	--	x	--	6 3/4	x	36	--	x	--	5 1/8	x	39	6 3/4	x	33
W 18 x 50	--	x	--	--	x	--	6 3/4	x	37 1/2	--	x	--	5 1/8	x	40 1/2	6 3/4	x	34 1/2
W 21 x 50	--	x	--	--	x	--	6 3/4	x	39	--	x	--	--	x	--	5 1/8	x	40 1/2
W 18 x 55	--	x	--	--	x	--	6 3/4	x	40 1/2	--	x	--	--	x	--	5 1/8	x	40 1/2
W 21 x 62	--	x	--	--	x	--	6 3/4	x	46 1/2	--	x	--	--	x	--	6 3/4	x	40 1/2

Table Specifications:

These sizes are for dry service condition of use.

Reverse use of this table to convert from glued laminated timber sizes to steel sections is non-conservative in all cases and is **NOT PERMITTED**.

Smaller glued laminated timber sizes may be possible with engineering calculations based on actual span and loading conditions.

Glued laminated timber beam sizes are based on a span to depth (L/d) ratio of 21. When the span to depth ratio is larger, sizes should be determined by engineering calculations.

To determine glued laminated timber beam sizes, E_{av} was adjusted by the volume factor. It is assumed that all beams are adequately braced for lateral stability.

Tabulated beam sizes have been checked for adequacy in flexure and deflection. It is the responsibility of the designer to check for adequacy in shear.

Tabulated beam sizes have been checked for adequacy in flexure and deflection. It is the responsibility of the designer to check for A minimum glued laminated timber depth of 6 inches is used in this table. Standard glued laminated timber sizes are used in this table.

While these design conversions have been prepared in accordance with recognized engineering principles and are based on accurate technical data, aluminum glued laminated timber depth of 6 inches is used in this table. Standard glued laminated timber sizes are used in this table.

While these design conversions have been prepared in accordance with recognized engineering principles and are based on accurate technical data, they should not be used without competent examination and verification of the accuracy, suitability, and applicability by a qualified design engineer.

ATC MAKES NO REPRESENTATION OR WARRANTY, EXPRESSED OR IMPLIED, THAT THE INFORMATION CONTAINED HEREIN IS SUITABLE FOR

ATTC MAKES NO REPRESENTATION OR WARRANTY, EXPRESSED OR IMPLIED, THAT THE INFORMATION CONTAINED HEREIN IS SUITABLE FOR ANY GENERAL OR SPECIFIC USE OR IS FREE FROM INFRINGEMENT OF ANY PATENT OR COPYRIGHT. ANY USER OF THIS INFORMATION ASSUMES ALL RISK AND LIABILITY ARISING FROM SUCH USE.